

Faster, deeper cures when compared to blue fluorescing materials

- Easy product authentication
- Accurate bond-line inspection
- Vivid color contrasts on blue fluorescing substrates
- Colorless when not exposed to UV
- Medical-grade products available
- LED-curable formulations available

Red Fluorescing Light-Curable Materials

Ultra-Red® fluorescing technology, formulated into Dymax light-curable adhesives and coatings, enhances bond-line inspection processes and product authentication. The uncured or cured adhesive or coating remains colorless until exposed to low-intensity UV light (360-380 nm), at which point it will fluoresce bright red. This is particularly effective while bonding plastics, like PVC and PET, which naturally fluoresce blue. The Ultra-Red® fluorescence does not absorb the same wavelengths as those used to cure the adhesive, resulting in faster, deeper cures when compared to blue fluorescing products.

The patented Ultra-Red[®] fluorescing compound is exclusive to Dymax for use in light-curable adhesives and coatings. When measured, this compound produces a unique energy peak that cannot be reproduced by other fluorescing compounds. This offers manufacturers the ability to assemble or mark their products so they can be positively identified. Ultra-Red[®] technology may be formulated into new or existing Dymax materials.



Materials formulated with Ultra-Red technology are colorless when not exposed to UV light.



Under low-intensity UV light, Ultra-Red materials fluoresce bright red, enabling easy bond-line inspection.



•••••

.

©2020 Dymax Corporation. All rights reserved. All trademarks in this guide, except where noted, are the property of, or used under license by, Dymax Corporation, USA.
Technical data provided is of a general nature and is based on laboratory test conditions. Dymax does not warrant the data contained in this bulletin. Any warranty applicable to
the product, its application and use, is strictly limited to that contained in Dymax's standard Conditions of Sale. Dymax does not assume responsibility for test or performance results
obtained by users. It is the user's responsibility to determine the suitability for the product application and purposes and the suitability for use in the user's intended manufacturing
apparatus and methods. The user should adopt such precautions and use guidelines as may be reasonably advisable or necessary for the protection of property and persons.
Nothing in this bulletin shall act as a representation that the product use or application will not infringe a patent owned by someone other than Dymax or act as a grant of license
under any Dymax Corporation Patent. Dymax recommends that each user adequately test its proposed use and application before actual repetitive use, using the data contained in
this bulletin as a general guide.
Stough 3/18/2021